




Standard Features

- Stake Pockets
- Scissor Hoist – Power Up / Power Down
- Adjustable Coupler
- Aluminum Toolbox
- 110V Battery Charger
- 10W Solar Panel
- PPG DTM 2 Part Epoxy Paint
- Fully Enclosed Wiring
- HSS Structural Tubing
- Engineered Sill Design
- Spare Tire*
- Galvanized Steel Slide in Ramps*
- Roll Up Tarp*
- Rear Drop Down Stabilizer Jacks*
- Side Boards*

*Dealer Specific Options

Specifications

Axle:	(2) 7,000 lb. Lippert Spring	Floor & Wall:	10ga Floor / 12ga Wall
Hoist:	Champion CS515T 7 Ton	Frame:	6 X 2 HSS
Jack:	7,000 lb. Top Wind Bolted	Lights:	LED
Ramp:	(2) 4,000 lb. Midspan Ramps (65 lbs. each)	Electric Plug:	7 Wire RV
Wheels:	235/80R16 E Steel	Safety Chains:	16,200 lb.
Tailgate:	Steel Barn Door	Paint Specs:	PPG 2-Part Epoxy DTM
Coupler:	21,000 lb. Demco Adjustable	Dump Angle:	45°



Dimensions

Model	A	B	C	D	E	F	G	Box Width
SL714-14K	60 1/2"	109"	169 1/2"	175 1/2"	25 1/4"	227 1/2"	164 3/8"	82"

Model	Description	Net Weight	GVWR	Payload Cap.
SL714-14K	7' x 14' 14,000 lb. Tandem Axle Black/Charcoal	3,120 lb.	15,400 lb.	12,280 lb.



Specs are subject to change without notice. Please contact Southland Trailers Product Specialist for price confirmation on all Products. - Revised June 2025